



## DC: DinoKoll Tile

One-component cement-based adhesive for indoor and outdoor installation of single and double fired materials on cement-based substrates.



### • DC:

- DC is abbreviation of Dinokoll Tile adhesive for Ceramic corresponds EN12004 in C1class.
- C1: standard setting cement-based adhesive.

### • Application:

- To install all types of floor ceramic tiles for indoor use.
- To install all types of cement and brick blocks.

### • Advantages:

- Easy to prepare and apply

### • Consumption:

- The best pulling adhesive with notched trowel and back of tile with thin spatula.
- The thickness should not more than 10 mm and 3-4 kg/m<sup>2</sup> for one side and 4-5 kg/m<sup>2</sup> for both side in small size and 5 kg/m<sup>2</sup> for both side in medium size and 4-5 kg/m<sup>2</sup> for one side and 6 kg/m<sup>2</sup> in both side in bigger, and the water ratio is about (22% - 24%) weight of adhesive.

Initial tensile adhesion strength (after 28 days)	>0.5 N/mm <sup>2</sup>
Tensile adhesion strength after heat ageing	>0.5 N/mm <sup>2</sup>
Tensile adhesion strength after water immersion	>0.5 N/mm <sup>2</sup>
Tensile adhesion strength after freeze-thaw cycle	>0.5 N/mm <sup>2</sup>
Open time	20 min

